



NOVOTEST

Leeb Hardness Tester NOVOTEST T-D2

High-precision, easy in operation and reliable with the most affordable price in the world among the analogues!

- ☑ Leeb probe
- ☑ Wide range of hardness value
- ☑ Minimum number of imprints
- ☑ Ease in operation
- ☑ Control of the batteries
- ☑ Graphical display with backlight
- ☑ Rubber protective housing-case
- ☑ New, intuitive menu with tips on the buttons
- ☑ Extended temperature range (-40 ... +50 °C)
- ☑ Leeb method, standardized according to ASTM A596



Description of Leeb Hardness Tester NOVOTEST T-D2:

Leeb Hardness Tester NOVOTEST T-D2 is designed for rapid non-destructive testing of hardness:


- metals and alloys on standardized hardness scales;
- metals with different properties from steel (for example, non-ferrous metals, alloys, cast iron, etc.) with additional scales for calibration;
- use of the scale of tensile strength (Rm) for determining the tensile strength of carbon steel products pearlitic by automatically converting from the scale of hardness Brinell (HB).



Portable hardness tester T-D2 very easy in operation, has the main functions with the lowest price in the world among the portable Leeb hardness testers!

The device works with dynamic (Leeb) probe.

Dynamic (**Leeb**) probe is used for measuring the hardness of non-ferrous metals, cast iron, coarse-grained materials, massive products etc



Has basic modes of measurement:

- Normal mode




- Statistics mode

	ST HB
Maximum	112.0
Minimum	93.0
Deviation	6.8
Average	104.0
Num. of meas.	6

- Smart mode



- Signal mode





Sealed housing with rubber protective strips - Hardness testers is ideal for use in workshop and field conditions with high humidity, dust, etc. Hardness tester has frost-resistant display that allows user to use the device at any season and in any climatic zone of the Earth.

Leeb Hardness Tester NOVOTEST T-D2 specifications:


Leeb probe types	D, DC, DL, C, D+15, E, G
Indenter	Hardened ball
Measuring direction	Any direction 360°
Measurement hardness range: - Rockwell, HRC - Brinell, HB - Vickers, HV - temporary resistance (tensile strength), MPa	20 - 70 90 - 450 230 - 940 370 - 1740
Measuring accuracy	HV+ / - 3%; HRC+ / - 1,5%; HB+ / - 3%;
Hardness scale	HRC, HB, HV, MPa
Materials	- Leeb probe - pre-calibrated for steel, alloy steel, cast iron, stainless steel, aluminum, bronze, brass, copper. - Additional custom materials for calibration.
Operating temperature range, ° C	-40 to +50
Power supply	2 AA batteries
Dimensions, mm	120x60x25
Weight of electronic unit with batteries, no more, kg	0.2
Batteries life, not less, h	20



NOVOTEST



The device has PC software with a comfortable and intuitive interface





The advantages of Hardness Tester NOVOTEST T-D2:

- ☑ Allows to test products with weight >5 kg and thickness >10mm
- ☑ Wide range of hardness
- ☑ Only basic functions, nothing extra
- ☑ Possibility to use in field conditions with high humidity and dust
- ☑ Convenience and ease of measurement
- ☑ Optimized number of buttons
- ☑ Contrast display with bright back-lighting
- ☑ Calibrations stored in memory of probe
- ☑ Very easy in operation and calibration
- ☑ Internal memory and communication with PC
- ☑ New, intuitive menu with tips on the buttons
- ☑ Extended temperature range (frost, down to - 40°C)
- ☑ Water resistant case
- ☑ Rubber bumper protected case
- ☑ High measurement accuracy





Standard set of Leeb Hardness Tester NOVOTEST T-D2

- Electronic block
- Leeb probe
- 2 batteries AA
- Charger
- USB cables
- Operating manual
- Software for PC
- Case



Available options for ordering of Leeb Hardness Tester NOVOTEST T-D2

- UCI probe (+activation code)
- Batteries
- Charger
- USB-cable
- Set of measures of hardness
- Case



Using the Leeb Hardness Tester NOVOTEST T-D2:

