

X-SERIES™**DUAL-LIGHT™ ANGLE LIGHT****RECHARGEABLE****ITEM NUMBER/UPC**

XPR-5568RX (Red), 0 17398 80631 2
 XPR-5568RXLB (Red, Light & Battery Only), 0 17398 80697 8
 XPR-5568GX (Green), 0 17398 80630 5

CERTIFICATIONS

- CE, cULus, Atex, IECEx, INMETRO, Meets requirements of NFPA

PATENTS

- 9,713,217 10,119,663

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 200L, 7 hrs. runtime
- MEDIUM: 110L, 15 hrs. runtime
- LOW: 60L, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime
- MEDIUM: 40L, 15 hrs. runtime
- SURVIVAL: 20L, 27 hrs. runtime

DUAL-LIGHT

- 205L, 7 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 10.6 oz (301g)(with batteries)

BATTERY

- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 12VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	200 LUMENS	100 LUMENS	205 LUMENS
	7h	7h	7h
	401m		
	40256cd		
	2m		
	1m		

Bayco Products, Inc. XPR-5568
 640 S. Sanden Blvd., Wylie, TX 75098

For use with Bayco Li-ion Battery Pack 5568-BATT or 5566-CARRIER with 3 AA Energizer Type EN91 or E91 batteries only

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T4 Ga
Ex ia op is I Ma
Ex ia op is IIC T4 Ga
DEMRO 17 ATEX 1927
IECEx UL 17.0082
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell Alkaline
3.7V/Cell Li-ion
IP-67
Um: 10V

UL LISTED
 E 467756
 ID 4003544
 ELECTRICAL SAFETY
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE
CE 2575
 Control Drawing: 5568-CERT-DWG1-03

Sequence




AVAILABLE IN MULTIPLE COLORS.